

H-09-16 H-11-11

SAE The Engineering Society
For Advancing Mobility
Land Sea Air and Space®
INTERNATIONAL

400 Commonwealth Drive, Warrendale, PA 15096-0001

AEROSPACE MATERIAL SPECIFICATION

SAE AMS-3138/6**REV****A**

Issued 1980-10-15
Revised 1990-07-01

Submitted for recognition as an American National Standard

COATING MATERIAL, FLUOROCARBON (FKM) ELASTOMERIC Anti-Static Topcoating, Gray

1. SCOPE:

- 1.1 Form: This specification covers a fluorocarbon (FKM) elastomeric coating material for fiber-reinforced-resin composite structures in the form of a two-component, brushable or sprayable liquid.
- 1.2 Application: Primarily as a topcoating over AMS-3138/1, AMS-3138/2, or AMS-3138/3 base coating for protection of aircraft and missile radomes and other components from rain-erosion, aerodynamic heating, static, and weathering.

2. APPLICABLE DOCUMENTS: See AMS-3138.

3. TECHNICAL REQUIREMENTS:

- 3.1 Basic Specification: The complete requirements for procuring the coating material described herein shall consist of this document and the latest issue of the basic specification AMS-3138.
- 3.2 Material: Shall be as specified in AMS-3138.
- 3.2.1 Color: Shall be gray and of sufficient intensity to hide completely the surface of the substrate, and shall closely match the applicable color chip of FED-STD-595.
- 3.3 Cured Coating Properties: Coating materials, mixed and cured as specified in the basic specification and applied over AMS-3138/1, AMS-3138/2, or AMS-3138/3, shall conform to the following requirements, determined in accordance with test methods listed in AMS-3138.

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.