


REV.
A

AS85049/92

FEDERAL SUPPLY CLASS
5935


THE REQUIREMENTS FOR ACQUIRING THE PRODUCT DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION: AS85049.



INCH	MM
.06	1.52
.09	2.29
.375	9.53
.660	16.76

FIGURE 1 - CONFIGURATION AND DIMENSIONS

THIRD ANGLE PROJECTION



CUSTODIAN: SAE AE-8/AE-8C1

SAE Aerospace
An SAE International Group**AEROSPACE STANDARD**

CONNECTOR ACCESSORIES, COMPOSITE, ELECTRICAL,
STRAIN RELIEF, 90°, SELF-LOCKING,
CATEGORY 4C
(FOR MIL-DTL-38999 SERIES III AND IV CONNECTORS)

AS85049/92
SHEET 1 OF 3**REV.**
A

Copyright © 2004 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Fax: 724-776-0790

Tel: 724-776-4970 (outside USA)
Email: custsvc@sae.org

SAE WEB ADDRESS: <http://www.sae.org>

ISSUED 2000-06 REVISED 2004-09

SHELL SIZES AND DIMENSIONS

SHELL SIZE	A MAX DIA	B MAX	C ±.031 DIA SEE NOTE 5	H ±.062	K MAX	M ±.03	SCREW SIZE SEE NOTE 6	G MAX
09	.858 (21.79)	.980 (24.89)	.219 (5.56)	.875 (22.23)	1.06 (26.92)	.375 (9.53)	4-40	.769 (19.53)
11	.984 (24.99)	1.05 (26.67)	.264 (6.71)	.937 (23.80)	1.10 (27.94)	.375 (9.53)	4-40	.792 (20.12)
13	1.157 (29.39)	1.20 (30.48)	.344 (8.74)	1.031 (26.19)	1.18 (29.97)	.406 (10.31)	6-32	.847 (21.51)
15	1.280 (32.51)	1.30 (33.02)	.460 (11.68)	1.125 (28.58)	1.30 (33.02)	.406 (10.31)	6-32	.890 (22.61)
17	1.406 (35.71)	1.42 (36.07)	.545 (13.84)	1.312 (33.32)	1.38 (35.05)	.406 (10.31)	6-32	.941 (23.90)
19	1.516 (38.51)	1.52 (38.61)	.615 (15.62)	1.375 (34.93)	1.45 (36.83)	.406 (10.31)	6-32	.972 (24.69)
21	1.642 (41.51)	1.64 (41.66)	.698 (17.73)	1.500 (38.10)	1.54 (39.12)	.406 (10.31)	6-32	1.009 (25.63)
23	1.768 (44.91)	1.77 (44.96)	.780 (19.81)	1.625 (41.28)	1.62 (41.15)	.406 (10.31)	6-32	1.050 (26.67)
25	1.890 (48.01)	1.89 (48.01)	.850 (21.59)	1.750 (44.45)	1.69 (42.93)	.406 (10.31)	6-32	1.085 (44.45)

FIGURE 1 - CONFIGURATION AND DIMENSIONS (CONTINUED)

NOTES:

- DIMENSIONS ARE IN INCHES.
- METRIC EQUIVALENTS ARE GIVEN FOR GENERAL INFORMATION ONLY.
- MILLIMETERS ARE IN PARENTHESES.
- DIMENSIONS APPLY AFTER PLATING.
- CABLE ENTRY IS MEASURED WITH SADDLE BARS CLOSED AND BOTTOMED ON CLAMP EARS.
- SCREW ASSEMBLY IAW: NAS720C4-6 OR NAS720C6-6 OR EQUIVALENT.
- PART SUPPLIED WITH DETENTED SELF-LOCKING WHICH PROVIDES A POSITIVE AUDIBLE DETENTED COUPLING, OPTION 'N' IS A FREE SPINNING SELF-LOCKING COUPLING.

REQUIREMENTS:

DESIGN AND CONSTRUCTION:

DIMENSIONS AND CONFIGURATION: SEE FIGURE 1.

INTERFACE DIMENSIONS: IN ACCORDANCE WITH AS85049, FIGURE 3.

ACCESSORY: CONSIST OF A COUPLING NUT, CLAMP STRAIN RELIEF, AND SADDLE BAR. THE COUPLING NUT SHALL BE CAPTIVATED TO THE CLAMP AND IS FREE TO ROTATE. ACCESSORIES WILL NOT ACCOMMODATE CONNECTORS USING SIZE 8, 4, OR 0 CONTACTS.

CLAMP SHALL HAVE NO PROTRUSIONS OR SHARP EDGES WHICH MAY PINCH CABLE.